


NOTES:
 1. EACH WORD TO BE CENTERED WITHIN LANE.
 2. LEGENDS SHALL BE WHITE.



GENERAL NOTES:

1. ALL RPM'S SHALL BE PLACED ON THE ISLAND SIDE OF THE ADJACENT EDGELINES.
2. INSTALL 24"X30" SPEED LIMIT SIGN W/21" X 15" M6-2L PANEL ON UPPER PART OF CONCRETE ISLAND UPSTREAM OF BOOTH. SIGN SHALL BE MOUNTED CENTERED ON ISLAND WITH A 7" CLEARANCE UNDER SIGN TO PAVEMENT. SIGN SHALL BE ROTATED 22 1/2 DEGREES TOWARDS DEDICATED SUNPASS LANE OR AS DIRECTED BY THE ENGINEER.
3. A COMPUTER DISK OF SUNPASS SIGNS IS AVAILABLE FROM THE DEPARTMENT.
4. PAVEMENT MARKINGS MAY BE ADJUSTED SLIGHTLY AS DIRECTED BY THE ENGINEER.
5. TOLL COLLECTOR WARNING SIGNS SHALL BE FURNISHED AND INSTALLED (ANCHOR BOLTED) BY THE CONTRACTOR ON THE ISLAND BARRIER WALL AND ON BOOTH FACING EACH STAIRWELL OR WALKWAY ACROSS ISLAND. SIGNS ATTACHED TO BOOTH SHALL BE FASTENED WITH STAINLESS STEEL SCREWS. PLACEMENT SHALL PROVIDE OPTIMUM VISIBILITY.
6. SIGNS SHALL BE MOUNTED ONLY ON ISLANDS BORDERING SUNPASS DEDICATED LANES.
7. SIGN ION CONCRETE ISLAND TO BE FASTENED ON VERTICAL CONCRETE WALL WITH LAG SHIELDS. SIGN SHALL BE MOUNTED SO AS TO NOT OBSTRUCT ELECTRIC OUTLETS, JUNCTION BOXES, OR CONTROL CABINETS.
8. SIGN ION CONCRETE BOOTH SHALL BE MOUNTED ABOVE WINDOW NEXT TO BOOTH DOOR AND CENTERED ON CONCRETE COLUMN. SIGN SHALL BE MOUNTED WITH LAG SHIELDS. CLEARANCES SHALL COMPLY WITH INDEX 17302.
9. SIGN 1 SHALL BE POST MOUNTED ADJACENT TO SIDEWALK BETWEEN ADMINISTRATION BUILDING AND NEAREST TOLL LANE.
10. FLEXIBLE DELINEATORS SHALL BE 48" HIGH, WHITE WITH 3" X 12" REFLECTIVE STRIP. THE DELINEATOR SHALL BE SURFACE MOUNTED ON EXISTING PAVEMENT.

RAMP PLAZA NOTES:

1. LEFT SIDE DEDICATED LANE SHALL BE MIRROR-IMAGE OF THIS EXHIBIT.
2. FOR DEDICATED LANE BETWEEN CONVENTIONAL TOLL COLLECTION LANES, CHANNELIZATION ISLANDS SHALL BE PLACED ON BOTH SIDES OF DEDICATED LANE.
3. TPK-V2 TO BE INSTALLED AT SUNPASS EQUIPPED PLAZAS.
4. IF 125' CHANNELIZATION IS ACHIEVED AFTER THE TOLL PLAZA, THE RI-2 SIGN IS NOT NEEDED.
5. FOR MIXED USE LANE MODIFY EXISTING CANOPY SIGN OR DESIGN NEW SIGN PANEL TO INCLUDE SUNPASS LOGO AND TOLL COLLECTOR SYMBOLS.
6. TOLL COLLECTOR SIGNS SHALL BE INSTALLED ON ISLANDS BORDERING DEDICATED USE SUNPASS LANES ONLY.
7. FOR A DEDICATED LANE ON THE OUTSIDE OF THE PLAZA AND WITH AN EXISTING LANE WIDTH OF TWELVE FEET OR GREATER, THE CHANNELIZATION ISLAND SHALL BE WIDENED ONE FOOT FROM WHAT IS SHOWN ABOVE TO PROVIDE A MINIMUM LANE WIDTH OF ELEVEN FEET.
8. FOR A DEDICATED LANE IN THE INTERIOR OF THE PLAZA AND WITH AN EXISTING LANE WIDTH OF TWELVE FEET OR GREATER, THE ADJACENT CHANNELIZATION ISLANDS SHALL BE WIDENED TO NARROW THE DEDICATED LANE TO TEN FEET.

STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION
TURNPIKE ENTERPRISE TRAFFIC DESIGN

RAMP TOLL PLAZA TYPICAL SUNPASS SIGNING AND PAVEMENT MARKINGS

Names	Dates	Approved By		
Designed By				
Drawn By				
Checked By				
		Revision No.	Sheet No.	Drawing No.
			1 of 2	105

g:\turnpike\special\pph\pph-plan.dgn