

GENERAL TOLLING REQUIREMENTS

PART 3 – PLANS PRODUCTION **JULY 2019**



Table of Contents

Table of Contents	ii
Exhibits	iv
300 Toll Submittal Requirements	1
300.1 General.....	1
300.2 Sheet Borders.....	2
301 Toll Facility Plans Component Sheets.....	3
301.1 Master Key Sheet	3
301.2 Signature Sheet.....	4
301.3 Toll Site Location Map	5
302 Sub-Components of Toll Facility Plans.....	6
302.1 Sub-Component Key Sheets	6
302.2 Toll Site Demolition / Renovation Plans.....	6
302.2.2 Index of Sheets for Demolition / Renovation Plans (per site)	8
302.3 Toll Facility Site Plans	11
302.3.1 Site Civil	11
302.3.2 Site Electrical.....	13
302.3.3 Index of Toll Site Plans (each site)	15
302.4 Toll Facility Building Plans	18
302.4.1 Architectural Plans.....	18
302.4.2 Structural Plans and Calculations.....	19
302.4.3 Mechanical Plans	20
302.4.4 Electrical Plans.....	20
302.4.5 Index of Toll Facility Building Plans (per building type).....	24

302.5	Non-Accessible Gantry Plans	27
302.5.1	Non-Accessible Gantry Structural Plans.....	27
302.5.2	Non-Accessible Gantry Electrical Plans	28
302.5.3	Index of Non-Accessible Gantry Plans (each gantry)	29
302.6	Accessible Gantry Plans.....	32
302.6.1	Accessible Gantry Structural Plans	32
302.6.2	Accessible Gantry Electrical Plans	33
302.6.3	Index of Accessible Gantry Plans (each gantry)	34
303	Phase Submittals for Conventional Projects	39
303.1	General.....	39
303.2	Phase I Submittal	40
303.3	Phase II Submittal	41
303.4	Phase III Submittal	46
303.5	Phase IV Submittal	47
303.6	Permit Plans	47
304	Phase Submittals for Non-Conventional Projects.....	48
304.1	General.....	48
304.2	Technical Proposal Submittal	49
304.3	90% Plans Submittal	51
304.4	Final Plans Submittal	55
304.5	Permit Plans	55
305	Design Analysis Reports	56
305.1	General.....	56
305.2	Mechanical Design	56

305.3 Electrical Design.....	57
306 Pay Items	60
306.1 General.....	60
307 Technical Special Provision Sections Updates	62
307.1 General.....	62
308 Shop Drawings	63
308.1 General.....	63

Exhibits

Exhibit 301.1-1 Toll Facility Plans Master Key Sheet Layout	4
Exhibit 301.3-1 Toll Site Location Map Layout	5
Exhibit 302.2-1 Demolition / Renovation Sheet Numbering Convention	8
Exhibit 302.3-1 Site Sheet Numbering Convention	15
Exhibit 302.4-1 Toll Facility Building Plans Sheet Numbering Convention.....	24
Exhibit 302.5-1 Non-Accessible Gantry Sheet Numbering Convention.....	29
Exhibit 302.6-1 Accessible Gantry Sheet Numbering Convention	34
Exhibit 303.1-1 Summary of Phase Submittals for Conventional Projects	39
Exhibit 304.1-1 Summary of Phase Submittals for Non-Conventional Projects	48

300 Toll Submittal Requirements

300.1 General

- (1) The Toll Facility Plans component is comprised of a series of sub-component plan sets. Each sub-component plan set must be prepared as described herein.
- (2) Each sub-component plan set includes a key sheet with the sub-component index of sheets.
- (3) A Google Earth ready KMZ/KML file must be prepared and submitted to FTE with each toll project. The file must have both existing and proposed information for each discipline. KMZ/KML files must be created in the format described in FTE's KMZ Deliverable Standards, which is located at:
<http://www.floridasturnpike.com/design/disciplines/roadway.html>
- (4) The requirements provided in **GTR Part 3** and the **FDOT** CADD Manual form the basis for contract plans format and assembly.
- (5) When integrated 3D models are required, the Toll Site must be fully integrated into the adjacent roadway model.
- (6) **GTR Part 3** includes additional requirements for assembly of toll facility related TSP section updates and calculations.
- (7) Prerequisites
 - (a) The Preliminary TSTM for the preferred alternative must be developed during the PD&E.
 - (b) The Draft TSTM must be developed from the Preliminary TSTM during 15% Line and Grade development.
 - (c) All outstanding comments must be resolved in the Final TSTM and accepted by FTE Tolls Design prior to Phase II submittal.
 - (d) All GTR deviations must be approved by FTE Tolls Design prior to Phase III submittal.

Modification for Non-Conventional Projects:

Delete **items (a), (b), (c), and (d)** above and replace with the following:

- (a) The Final TSTM is developed during RFP Development phase.
- (b) A revised Final TSTM is required where identified in **GTR 202**.
- (c) All GTR deviations must be approved by FTE Tolls Design prior to 90% plans submittal.

300.2 Sheet Borders

All sheets, other than the Key Sheet, must use the Structures Border cell “Sheet-Border” as identified in the **FDOT [CADD Manual](#) Section 7.6.8.1**.

The border has two types of numbering:

- (1) Sheet Number – This starts with the master key sheet as sheet number 1 and is consecutive through the master plan set, continuing through all the sub-component plan sets. All sheets of the sub-component set for a toll site must be numbered consecutively.
- (2) Drawing Number – Each sheet of the toll facilities component set has a unique drawing number based on the sub-component, and type of drawing. See **GTR 302** and [Exhibit 302.2-1](#), [Exhibit 302.3-1](#), [Exhibit 302.4-1](#), [Exhibit 302.5-1](#), and [Exhibit 302.6-1](#) for additional information on drawing numbering requirements.


301 Toll Facility Plans Component Sheets

301.1 Master Key Sheet

The Toll Facility Plans Master Key Sheet must be prepared in accordance with **FDM 302** and include following:

- (1) GTR criteria version used for design.
- (2) Additional drawing number block. See [Exhibit 301.1-1](#).
- (3) Index of Toll Facilities Master Plans
 - (a) Toll Facility Plans Master Key Sheet, numbered TF-001.
 - (b) Signature Sheets must begin numbering at TF-002 and be numbered sequentially.
 - (c) Toll Site Location Map must be numbered sequentially TF-00#, beginning with the next number following the signature sheets.
- (4) Toll Facility Plans sub-component plans must be listed above the “Index of Toll Facilities Master Plans. The sub-component plans must be included in the following order:
 - (a) Toll Facilities Demolition / Renovation Plans
 - (b) Toll Facilities Site Plans
 - (c) Toll Facilities Building Plans
 - (d) Toll Facilities Gantry Plans

Exhibit 301.1-1 Toll Facility Plans Master Key Sheet Layout

<p>TOLL FACILITIES PLANS SUBCOMPONENTS</p> <p>TOLL FACILITIES DEMOLITION PLANS TOLL FACILITIES SITE PLANS TOLL FACILITIES BUILDING PLANS TOLL FACILITIES GANTRY PLANS</p> <p>A DETAILED INDEX APPEARS ON THE KEY SHEET OF EACH SUBCOMPONENT</p> <p>INDEX OF TOLL FACILITIES MASTER PLANS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>SHEET NO.</th> <th>SHEET DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>TF-001</td> <td>Toll Facilities Master Key Sheet</td> </tr> <tr> <td>TF-002</td> <td>Toll Facilities Master Signature Sheet (Not Included)</td> </tr> <tr> <td>TF-003</td> <td>Toll Site Location Map</td> </tr> </tbody> </table> <p>APPLICABLE DESIGN STANDARDS:</p> <p>GOVERNING STANDARDS AND TOLLING CRITERIA: GENERAL TOLLING REQUIREMENTS (GTR) DATED 2018 AS AMENDED BY CONTRACT DOCUMENTS.</p>	SHEET NO.	SHEET DESCRIPTION	TF-001	Toll Facilities Master Key Sheet	TF-002	Toll Facilities Master Signature Sheet (Not Included)	TF-003	Toll Site Location Map	<p>STATE OF FLORIDA DEPARTMENT OF TRANSPORTATION</p> <p>CONTRACT PLANS</p> <p>FINANCIAL PROJECT ID _____</p> <p>(_____)</p> <p>_____ COUNTY (_____)</p> <p>STATE ROAD NO. _____</p> <p>PROJECT DESCRIPTION WITH PROJECT LIMITS AND MILEPOST LIMITS</p> <p>TOLL FACILITIES PLANS</p>	 <p style="text-align: right;">TOLL FACILITY PLANS ENGINEER OF RECORD:</p> <p style="text-align: right;">FDOT PROJECT MANAGER:</p>						
SHEET NO.	SHEET DESCRIPTION															
TF-001	Toll Facilities Master Key Sheet															
TF-002	Toll Facilities Master Signature Sheet (Not Included)															
TF-003	Toll Site Location Map															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">KEY SHEET REVISIONS</th> </tr> <tr> <th>DATE</th> <th>DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td style="height: 40px;"></td> <td></td> </tr> </tbody> </table>		KEY SHEET REVISIONS		DATE	DESCRIPTION			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>CONSTRUCTION CONTRACT NO.</th> <th>FISCAL YEAR</th> <th>DRAWING NO.</th> <th>SHEET NO.</th> </tr> </thead> <tbody> <tr> <td>XXXXX</td> <td>XX</td> <td>TF-001</td> <td>1</td> </tr> </tbody> </table>	CONSTRUCTION CONTRACT NO.	FISCAL YEAR	DRAWING NO.	SHEET NO.	XXXXX	XX	TF-001	1
KEY SHEET REVISIONS																
DATE	DESCRIPTION															
CONSTRUCTION CONTRACT NO.	FISCAL YEAR	DRAWING NO.	SHEET NO.													
XXXXX	XX	TF-001	1													

THE OFFICIAL RECORD OF THIS SHEET IS THE ELECTRONIC FILE DIGITALLY SIGNED AND SEALED UNDER RULE 61015-23.004, F.A.C.

301.2 Signature Sheet


The toll facility plans component set must be signed and sealed digitally and delivered as one (1) PDF file. The Signature Sheet must be located immediately after the Toll Facility Plans Master Key Sheet.

The Signature Sheet for digitally signed and sealed documents includes signatures for all disciplines in all sub-component plans. The Signature Sheet must be prepared in accordance with **FDM 303**. See **FDM Exhibits 303-1** and **303-2** for signature sheet examples.

301.3 Toll Site Location Map

The toll site location map (project layout) must show the horizontal alignment, stationing and include a call out for each toll site in the project that includes the gantry types, station and milepost based on the centerline of the gantry(ies). See [Exhibit 301.3-1](#).

Exhibit 301.3-1 Toll Site Location Map Layout



302 Sub-Components of Toll Facility Plans

Sub-component plan sets must be provided for the following:

- Toll Facility Demolition / Renovation Plans (each site)
- Toll Facility Site Plans (each site)
- Toll Facility Building Plans (each building type)
- Toll Facility Gantry Plans (each gantry)

302.1 Sub-Component Key Sheets

A separate key sheet must be provided for each toll facilities sub-component plan set. Each key sheet base must be a copy of the master key sheet except for the following changes:

- (1) Identify the subcomponent's registered professional of record
- (2) Uniquely identify the sub-component set within the project
(e.g. Site 1; Building Type A; Gantry 1)
- (3) Identify the index of plans for that sub-component set

302.2 Toll Site Demolition / Renovation Plans


- (1) A separate sub-component plan set must be provided for each demolition site. Each demolition site must be identified by a consecutive and unique number. See [Exhibit 302.2-1](#) for details regarding the sheet number protocol.
 - (a) The demolition site number and description must be identified on the demolition sub-component plan key sheet as a sub-title.
 - (b) The sub-title must include the mile post and stationing of the demolition site.
 - (c) The title block on each sheet of the sub-component plan set must indicate the demolition site number.
- (2) The plans must include the following as needed for demolition / renovations:
 - (a) Site civil
 - (b) Site electrical
 - (c) Building architectural
 - (d) Building structural
 - (e) Building mechanical

- (f) Building electrical plans.
- (3) For demolition only sites, all electrical, mechanical and structural notes may be shown on the site civil demolition sheet if appropriate.
- (4) The plans must identify the limits of work, construction phasing required to maintain existing site operations prior to demolition, and the maintenance of traffic. This sub-component set must be developed for demolition permit applications.
- (5) The plans must identify the following:
 - (a) Details for structural, mechanical, and electrical demolition by stage of construction.
 - (b) Required protection or modification for any existing infrastructure to remain.
 - (c) Extent of demolition including removal of foundations and infill of below grade structures and/or utilities.
 - (d) Structures to remain.
 - (e) Areas where existing structures or utilities must be protected.

302.2.2 Index of Sheets for Demolition / Renovation Plans (per site)

The sheet numbering for the Demolition / Renovation Plans must be as shown below:

Exhibit 302.2-1 Demolition / Renovation Sheet Numbering Convention



Assemble the toll site demolition and/or renovation plans in the following order and format:

Sheet No. Sheet Description

DG-101	KEY SHEET
DG-102	GENERAL NOTES, LEGEND, AND PAY ITEMS – SITE 1
DSC-101	ABBREVIATIONS, SYMBOLS, AND DEMOLITION NOTES – SITE 1
DSC-111	OVERALL SITE DEMOLITION / RENOVATION PLAN – SITE 1
DSC-11#	SITE GRADING PLAN(S) – SITE 1
DST-11#	SITE CIVIL DEMOLITION / RENOVATION PLAN(S) PHASE #
DSE-11#	SITE ELECTRICAL DEMOLITION / RENOVATION PLAN(S) PHASE #
DSI-11#	ISLAND / LANE DEMOLITION / RENOVATION PLAN(S) PHASE #
DSM-11#	ISLAND / LANE MECHANICAL / PLUMBING DEMOLITION / RENOVATION PLAN(S) PHASE #
DSE-11#	ISLAND / LANE ELECTRICAL DEMOLITION / RENOVATION PLAN(S) PHASE #
DST-12#	CANOPY DEMOLITION / RENOVATION ELEVATION(S) PHASE #
DSI-13#	ISLAND / LANE DEMOLITION / RENOVATION SECTION(S)
DSS-15#	CANOPY DEMOLITION / RENOVATION DETAIL(S)
DAU-11#	OVERALL TUNNEL DEMOLITION / RENOVATION PLAN(S) (Structural) (Includes phased demolition of Structural and temporary shoring to support MOT phasing) – SITE 1
DAU-11#	OVERALL TUNNEL DEMOLITION / RENOVATION PLAN(S) (Mechanical / Plumbing) (Includes phased demolition of Mechanical and Plumbing systems to support MOT phasing) – SITE 1
DAU-11#	OVERALL TUNNEL DEMOLITION / RENOVATION PLAN(S) (Electrical) (Includes phased demolition of Electrical systems to support MOT phasing) – SITE 1
DAA-11#	BUILDING ARCHITECTURAL DEMOLITION / RENOVATION FLOOR PLAN(S)
DAS-11#	BUILDING STRUCTURAL DEMOLITION / RENOVATION FLOOR PLAN(S)

DAA-12#	BUILDING ARCHITECTURAL DEMOLITION / RENOVATION ELEVATION(S) – SITE 1
DAA-15#	BUILDING ARCHITECTURAL DEMOLITION / RENOVATION DETAIL(S) – SITE 1
DAM-11#	BUILDING MECHANICAL DEMOLITION / RENOVATION PLAN(S) – SITE 1
DAM-15#	BUILDING MECHANICAL DEMOLITION / RENOVATION DETAIL(S) – SITE 1
DAE-11#	BUILDING ELECTRICAL DEMOLITION / RENOVATION PLAN(S) – SITE 1
DAE-15#	BUILDING ELECTRICAL DEMOLITION / RENOVATION DETAIL(S) – SITE 1
DAE-16#	POWER RISER DIAGRAM(S) – SITE 1
DAE-16#	ELECTRICAL PANEL SCHEDULE(S) – SITE 1

302.3 Toll Facility Site Plans

- (1) A separate sub-component plan set must be provided for each site. Each site must be identified by a unique number starting at one (1). Site numbers must increment consecutively. See [Exhibit 302.3-1](#) for details regarding the sheet number protocol.
- (2) The following information must be included on the site plans:
 - (a) The site number along with the mile post and stationing of the toll site must be identified on the key sheet as a sub-title. Toll site stationing is based on the centerline stationing of the primary gantry.
 - (b) The title block on each sheet of the sub-component plan set must indicate the site number.
 - (c) The site plans for each sub-component set must include the site civil plans and the site electrical plans.
- (3) The following items must be included on all site plans.
 - (a) Building type and gantry no.(s).
 - (b) North arrow and scale.
 - (c) Baseline with stationing.
 - (d) Toll loop pavement area and toll site envelope limits.
 - (e) Existing and proposed roadway, lane striping, lane widths, direction of travel, tolling loop conduit stub-ups, all pull boxes, man holes and hand holes, service driveway(s), maintenance pull-off area(s), drainage systems, drilled shaft(s), column upright(s), ITS, lighting, utilities, and landscaping.
- (4) Site civil and site electrical plans must be presented at the following scales:
 - (a) Overall site plans at 1"=40' or 1"=50'.
 - (b) Enlarged site plans at 1"=20'
 - (c) Grading plans at 1"=20'
 - (d) Details must be at an appropriate scale.

302.3.1 Site Civil

Grading, drainage, geometry, parking, pavement, concrete slabs, signing, pull boxes, and sidewalks must be shown on the site civil plans. Site civil plans must be coordinated with all other drawings. Any items that impact the tolling site, associated buildings, gantries, or site infrastructure must be shown on the site civil plans. The site civil plans must show the following within the limits of construction:

- (1) Station and offsets for site elements (building corners, sidewalk corners, generator slab corners, screen wall, drywell, gantry and stair columns, transformer pad, etc.). This information may be shown separately on an additional site layout plan sheet or combined with the grading plan.
- (2) Site geometry including building dimensions, maintenance driveway geometry, equipment maintenance offsets for generator and fuel tank, transformer, pull box layout, and all other site element layouts.
- (3) Show lane striping and add call outs for each shoulder and each lane including the type of lane (GTL, GUL, EL). Provide lane numbering at each toll gantry starting with the NB/EB left lane as Lane 1. Provide shoulder numbering at each toll gantry starting with the NB/EB inside shoulder as Shoulder 1. Provide lane, shoulder and buffer widths.
- (4) Latitude and longitude callouts:
 - (a) The plans for new gantries must include the latitude and longitude callouts for the SunPass® Antenna System locations to comply with regulations and to receive a permit from the Federal Communications Commission (FCC).
 - (b) This information must be included in the first submittal of the toll site plans.
 - (c) The latitude and longitude of the gantry centerline must be provided in degrees, minutes, and seconds as well as the northing and easting with the datum for verification of each antenna system, centered on each tolling direction.
 - (d) The associated roadway's milepost, to the nearest tenth of a mile, must be included for reference.
 - (e) Separate call outs are required for each direction of travel.
- (5) The enlarged site plan must show the following:
 - (a) Maintenance driveway limits and the adjacent roadway shoulder.
 - (b) All site elements to scale including, but not limited to, pull boxes, mechanical equipment, gantry foundations, walls, wire troughs, dry well and bollards.
 - (c) Sidewalk and equipment foundations.
 - (d) Gravel limits.
 - (e) Adjacent drainage ditches and drainage structures
- (6) Spot elevations along the perimeter of the new construction, finished floor elevations, sidewalk elevations, all locations identified in item 2 above, and other areas pertinent to the drainage of storm water must be included. Spot elevations must also be shown on both sides of the barrier and where the maintenance driveway meets the roadway

- (7) Cross sections at critical site points showing grading must be provided. At a minimum, cross sections must show grading at the shoulder adjacent to the building, screen wall, generator pad, building, gantry, and maintenance driveway access. The cross sections must identify the maximum elevation difference between edge of shoulder and concrete sidewalk across the concrete barrier.
- (8) Grading for bollards, grading beyond sidewalk limits and grading for ditches, ponds and streams near the toll site. Grading details must be provided in accordance with **GTR 231.7**. Additional spot elevations must be included to demonstrate positive drainage when the area surrounding the building is relatively flat. Contours must be shown on the enlarged site plan and the contours may continue onto the overall site plan as needed to show the limits required.
- (9) The walls in plan must be located and the type of wall and railing / barrier features must be identified. Strap limits on plan for MSE walls must be shown.
- (10) A geotechnical engineer's report per **FDOT [Soils and Foundations Handbook](#)**.
- (11) Sidewalk expansion and contraction joint layout must be included.
- (12) Site civil details as required. These include, at a minimum:
 - (a) Toll site median concrete barrier pull box layout elevation and section details
 - (b) Sidewalk and concrete pad details and sidewalk joint details
 - (c) Bollard details
 - (d) Loop pull box details
 - (e) Equipment slab details

302.3.2 Site Electrical

The electrical infrastructure necessary to support the installation and operation of toll loops, generator, fuel tank, and wiring between gantry toll equipment and the building. The site electrical plans must show the following within the limits of construction:


- (1) Primary Service routing plan(s), showing the primary power extension from the utility point of presence at the limited access (LA) right-of-way (R/W) to each toll site primary transformer including the routing must be provided.
- (2) Cross sections showing the boring under the roadway must also be included, where applicable.

- (3) Overall site electrical plans, and enlarged site electrical plans must include, at a minimum:
 - (a) Site elements and all associated site conduits and their routing from origin to termination point.
 - (b) Site electrical equipment (e.g. pull box, ground well, wire trough, etc.).
 - (c) All transformer connections.
 - (d) Mechanical equipment with electrical connections.
 - (e) Proposed utilities near the toll site.
 - (f) Existing utilities to remain near the toll site.
- (4) Site electrical details as required including ground-mounted E6 cabinets and wiring diagrams.
- (5) Loop pull boxes must be labeled in the plans with a unique consecutive number (#) for each toll site beginning with 1. Each pull box label must be formatted with the following prefixes:
 - (a) Loop Pull Boxes – PB#
 - (b) Intermediate Loop Pull Boxes – IPB#
 - (c) Median Loop Pull Boxes – MPB#
- (6) Lightning protection plans showing counterpoise loops, bonding conductors, ground rods, points of bonding to metallic site elements, and related notes.

302.3.3 Index of Toll Site Plans (each site)

The sheet numbering for the site civil and site electrical plans must be as shown below:

Exhibit 302.3-1 Site Sheet Numbering Convention



Assemble the toll site plans in the following order and format:

Site Civil Plans

Sheet No.	Sheet Description	Scale
SG#-001	KEY SHEET AND INDEX OF SHEETS	
SG#-002	SIGNATURE SHEETS	
SG#-003	CIVIL GENERAL NOTES, LEGEND, AND PAY ITEMS	
SG#-004	TOLL SITE LOCATION MAP	
SC#-101	OVERALL CIVIL SITE PLAN SITE #	1" =40' or 1" = 50'
SC#-10#	ENLARGED CIVIL SITE PLAN(S) SITE #	1" =20'
SC#-10#	GRADING PLAN(S) SITE #	1" = 20'
SC#-301	GRADING SECTIONS SITE #	
SC#-501	MEDIAN CONCRETE BARRIER TRANSITIONS SITE #	
SC#-50#	CIVIL SITE DETAIL(S) SITE #	

Site Electrical Plans

SE#-001	ELECTRICAL SYMBOLS, LEGEND, AND ABBREVIATIONS	
SE#-00#	ELECTRICAL GENERAL NOTES	
SE#-101	OVERALL ELECTRICAL SITE PLAN SITE #	1" =20'
SE#-10#	ENLARGED ELECTRICAL SITE PLAN(S) SITE #	1" =5'
SE#-10#	LIGHTNING PROTECTION PLAN(S) SITE #	1" =20'
SE#-10#	PRIMARY SERVICE ROUTING PLAN(S) SITE #	
SE#-301	PRIMARY SERVICE ROUTING SECTION(S) SITE #	
SE#-501	ELECTRICAL SITE DETAIL(S) SITE #	
SE#-50#	ELECTRICAL SITE DETAIL(S) SITE #	

302.4 Toll Facility Building Plans

A separate sub-component plan set must be prepared for each unique toll equipment building. See [Exhibit 302.4-1](#) for details regarding the sheet number protocol.

- (1) Each unique building type must be identified by a unique alphabetic character starting at A.
- (2) The Key Sheet must also identify the toll site and gantry numbers that are supported by this building type.
- (3) The sheet title in the title block on each sheet must indicate the building type alpha character.
- (4) Each building sub-component set must include all necessary discipline's plans, architectural, structural, mechanical, and electrical plans, to be a complete standalone plan set.
- (5) The plans elevations and details must indicate the scale to which it is drawn.

302.4.1 Architectural Plans

The following items must be included on the toll sites architectural plans:

- (1) General Notes must include the State of Florida or Miami-Dade Product Approval Notice of Acceptances (NOA) for all exterior door and door frame assemblies, roof system, and parapet copings for the basis of designs shown in the plans.
- (2) Floor, reflected ceiling, and roof plans, exterior elevations, wall sections, details, and finish and hardware schedules as required to obtain a building permit.
- (3) Floor plans must be prepared according to the following requirements:
 - (a) Floor plans, drawn at an architectural scale that allows each entire site to be shown on one sheet, without break lines, and shows project phasing.
 - (b) The floor plans scale must be ¼-inch or larger showing typical spaces or special rooms with dimensions, showing doors, opening layouts, and other relevant features.
 - (c) Cross references must be included explaining the extent of work, wall types, or other components, assembly, or direction regarding the construction.
- (4) Reflected ceiling plans must be prepared according to the following requirements:
 - (a) Reflected ceiling plans scale must be ¼-inch or larger showing typical spaces or special rooms with dimensions and lighting equipment.
 - (b) Ceiling types, materials, heights, and light fixture types must be shown.

- (5) Roof plans must be prepared according to the following requirements:
 - (a) Roof plans scale must be ¼-inch or larger showing dimensioned penetrations, equipment, and other relevant features.
 - (b) All roof penetrations, including drains, lightning protection, and any other equipment on the roof, must be shown.
 - (c) The direction of roof slopes with elevations at the high and low points, type of roofing system to be used, typical parapet, and flashing details must be shown.
 - (d) Dimensions that locate all penetrations and cross-reference details.
- (6) Exterior building elevations plans must be prepared according to the following requirements:
 - (a) The scale, finish, size, and detail of the site must be shown. The details must include all exterior mounted equipment, doors, conduit, CCTV, or reveals as applicable to the building.
- (7) Wall sections plans must be prepared according to the following requirements:
 - (a) Dimensions, proposed construction material, fastener type, length, and spacing must be included.
 - (b) A comparison of finished floor to finished grades at the entrance must be included.
- (8) Details and appropriate schedules referencing manufacturer's numbers or catalogs, room finishes, hardware, and other construction characteristics must be prepared. Door jamb, head, and sill conditions must be included.
- (9) Any other specialized items may be included that are necessary to clearly show the intent of the project design.
- (10) Architectural must be coordinated with civil, structural, mechanical, and electrical disciplines.

302.4.2 Structural Plans and Calculations

Structural building plans and details, must be included in the toll facility structural building plans and must include the following:

- (1) Structural plans and elevations scale must be ¼-inch or larger showing dimensioned penetrations, and other relevant features. Details must be at a sufficiently large scale to clearly delineate the relevant information to be conveyed.
- (2) General notes for design loads, design codes, material related notes, abbreviations, legend and details.

- (3) Structural foundation plans showing the associated wind load diagrams, foundation block outs, schedules, notes, details, and sections.
- (4) Roof plans, elevations, sections and details showing all penetrations.
- (5) Wind load (roof uplift) diagrams and tables.
- (6) Screen wall sections, elevations, and details.
- (7) Equipment support frames' details as described in **GTR 241.6**.
- (8) Fuel tank tie-down details.

Structural calculations for toll facility buildings must include the following:

- (1) Structural calculations for all design criteria, dead load, and wind pressures for the pre-engineered precast concrete building, foundation system, screen wall designs, and equipment support frames as applicable.
- (2) The associated wind load diagrams and sections for all calculations, as applicable.
- (3) Fastener calculations to mount all ceiling, and wall-mounted equipment described in **GTR 241**, including fastener type, size and minimum embedment depth.

302.4.3 Mechanical Plans

Equipment schedules, floor plan, generator plan, fuel tank, and piping details as required to obtain a building permit must be included on the toll sites mechanical plans included the following:

- (1) Mechanical plans and elevations scale must be ¼-inch or larger. Details must be at a sufficiently large scale to clearly delineate the relevant information to be conveyed. Plans include general notes, floor plans, air conditioning (AC) equipment layout(s), and sections.
- (2) Fuel Oil plans to include fuel tank and piping plans, fuel tank sections, details, monitoring system details, and notes.
- (3) Mechanical equipment details including fuel pipe cover plate details and Fuel tank details.
- (4) Condensate drywell and AC condensate piping details.
- (5) AC Equipment Details and Schedule

302.4.4 Electrical Plans

Power distribution, lighting, lightning protection, SCADA, access control, CCTV, tolling equipment raceway plans, interior wall elevations, communication system, details, riser

diagrams, and panel schedules must be included on the toll facility electrical plans. The electrical plans must include the following:

- (1) Electrical symbol legend, abbreviations, and fixture schedule sheet for each separate plan set. This sheet must show the electrical symbols used in the plan set with corresponding definitions for each symbol. The (basis of design) fixture schedule must include fixture type, description, manufacturer model number, voltage, mounting orientation, and remarks required for design or installation.
- (2) Electrical plans and elevations scale must be ¼-inch or larger unless otherwise noted. Electrical details must be at a sufficiently large scale to clearly delineate the relevant information to be conveyed.
- (3) Power distribution system plans, scale must be ¼-inch. These plans must show the following:
 - (a) Physical location and approximate size of the electrical distribution system equipment.
 - (b) Power outlets.
 - (c) Feeders and raceways.
 - (d) Mechanical and plumbing equipment that require electrical service.
 - (e) The physical location of the driven ground rods serving the distribution system.
- (4) Lighting plans, scale must be ¼-inch. These plans must show the interior reflected ceiling of the building with scaled light fixture symbols shown at each location where a light fixture is installed. Equipment specified by other disciplines that may interfere with the light fixture's location must be shown on the plan such that coordination of physical locations occurs.

These plans must show the following:

- (a) Any exterior light fixtures.
- (b) The light fixture schedule.
- (c) Required mounting heights.
- (d) Light switches.
- (e) Lighting controls.
- (f) Branch circuit designations for the circuits that serve the lighting system.
- (g) Reference notes to indicate the calculated average lighting levels in each interior and exterior area.
- (h) A separate detail plan sheet for fixture mounting details, elevation details, and control wiring details as required.


- (5) Lightning protection plans scale must be ¼-inch and details. These plans must show the following on the same sheet:
 - (a) Building and outdoor equipment connected to the lightning protection system.
 - (b) Size of the lightning protection system conductors.
 - (c) Location of all air terminals, ground loops, bonding conductors, down conductors, and ground rods.
 - (d) Additional sheets for specific details of the lightning protection system components and interconnection between the site infrastructure, gantry, and toll equipment building.
- (6) SCADA, security, and access control systems plans, scale must be ¼-inch. Prepare a separate set of SCADA, security, and access control system plans for each building or site. The plans must include the following:
 - (a) SCADA system notes and block diagrams.
 - (b) Security, and access control system, wiring and riser diagrams, showing each sensor, meter, door hardware, components in the building, and on the toll site that are to be monitored.
 - (c) The size, quantity, and routing of the raceways required for each device.
 - (d) All electrical, SCADA, security and access control system plans coordinated with the interior wall elevations of the toll equipment building.
- (7) Tolling equipment raceway plans must be scaled at ¼-inch and must include the following:
 - (a) Size, type, and locations of the raceways that are used by a toll equipment contractor to install the tolling equipment.
 - (b) Raceways that require exact locations or stub up locations, dimensions from the walls, or other structural components.
 - (c) The exact location and size of the toll communication cabinet mounting frame.
- (8) Interior elevations, scale must be ¾-inch or larger. A detailed drawing must be prepared to scale for each wall in the toll equipment buildings. The elevation drawings must show the following:
 - (a) Actual physical dimensions required for the installation to assure proper integration of the equipment with other building systems while maintaining NEC required clearances.
 - (b) Locations of conduit, racking, junction boxes, panelboards, safety switches, UPS units, bypass switches, and wall mounted equipment.

- (c) Show the fiber optic communications conduits stubbed up under the toll's communications cabinet.
- (9) Toll equipment working space stub-up details.
- (10) Toll equipment cabinet isometric detail must show the required receptacles in the overhead cable tray for TEC equipment and the tolling communications cabinet.
- (11) Miscellaneous electrical details including emergency power shutoff details and diagrams, grounding riser, grounding bus and inspection well details, Access control wiring and raceway details, lightning protection down conductor details, wall-mounted device conduit and box details.
- (12) Power riser diagrams must include all devices from the power sources (utility transformer and generator) to the main and distribution panelboards including the following:
 - (a) Surge protection devices.
 - (b) Short circuit analysis.
 - (c) Feeder conduit and conductors' type and size.
 - (d) Emergency power off.
 - (e) Meter.
 - (f) Automatic transfer switch.
 - (g) Bypass switches.
 - (h) Disconnect switches.
 - (i) Uninterruptible power supply.
 - (j) Any distribution equipment in the system up to the last distribution panelboards with the branch circuits.
- (13) UPS / BPS one-line diagrams.
- (14) Panel schedules for all electrical panelboards within the toll equipment building and rooms where the limits of work are defined, must include the following:
 - (a) Surge protective devices, electric service configuration (voltage, phase, ground, and phase wires) including the minimum interrupt rating must be provided for all electrical panels.
 - (b) Each panel's schedule including breaker size, load, and load description.
 - (c) Load calculations for service and feeder conductors.

302.4.5 Index of Toll Facility Building Plans (per building type)

The sheet numbering for the toll facility building plans must be as follows:

Exhibit 302.4-1 Toll Facility Building Plans Sheet Numbering Convention



Assemble the toll facility building plans in the following order and format:

ARCHITECTURAL PLANS (BUILDING)

Sheet No.	Sheet Description	Scale
AA α -001	GENERAL NOTES, ABBREVIATIONS, SYMBOLS, AND LEGEND	
AA α -10#	FLOOR PLAN AND LIFE SAFETY INFORMATION	$\frac{1}{4}" = 1'$
AA α -10#	REFLECTED CEILING PLAN AND ROOF PLAN	$\frac{1}{4}" = 1'$
AA α -20#	EXTERIOR ELEVATIONS	$\frac{1}{4}" = 1'$
AA α -30#	WALL SECTIONS	$1 \frac{1}{2}" = 1'$
AA α -50#	DOOR DETAILS	
AA α -60#	BUILDING FINISH AND DOOR SCHEDULES	

STRUCTURAL PLANS (BUILDING)

AS α -001	GENERAL NOTES, ABBREVIATIONS, SYMBOLS, AND LEGEND	
AS α -00#	GENERAL NOTES (CONT.)	
AS α -10#	FOUNDATION PLAN AND SECTIONS	$\frac{1}{4}" = 1'$
AS α -10#	ROOF PLAN	$\frac{1}{4}" = 1'$
AS α -20#	EXTERIOR ELEVATIONS	$\frac{1}{4}" = 1'$
AS α -301	SECTIONS AND DETAILS	
AS α -30#	SECTIONS AND DETAILS	
AS α -50#	STRUCTURAL DETAILS FOR EQUIPMENT FRAMES	$\frac{1}{2}" = 1'$

MECHANICAL PLANS (BUILDING)

AM α -00#	GENERAL NOTES, ABBREVIATIONS, SYMBOLS, LEGEND, AND CODE DATA	
AM α -201	MECHANICAL FLOOR PLAN	$\frac{1}{4}" = 1'$
AM α -20#	MECHANICAL FUEL OIL PLAN	$\frac{1}{4}" = 1'$
AM α -50#	MECHANICAL FUEL OIL DETAILS	
AM α -50#	MECHANICAL CONDENSATE DETAILS	
AM α -60#	AC EQUIPMENT SCHEDULE	

ELECTRICAL PLANS (BUILDING)

Sheet No.	Sheet Description	Scale
AE α -00#	ELECTRICAL SYMBOLS, LEGEND, AND ABBREVIATIONS	
AE α -00#	ELECTRICAL GENERAL NOTES	
AE α -101	POWER PLAN	$\frac{1}{4}" = 1'$
AE α -10#	LIGHTING PLAN	$\frac{1}{4}" = 1'$
AE α -10#	LIGHTNING PROTECTION PLAN	$\frac{1}{4}" = 1'$
AE α -10#	SCADA AND SECURITY SYSTEM PLANS	$\frac{1}{4}" = 1'$
AE α -10#	TOLLING EQUIPMENT RACEWAY PLAN	$\frac{1}{4}" = 1'$
AE α -201	INTERIOR ELEVATIONS	$\frac{3}{8}" = 1'$
AE α -20#	INTERIOR ELEVATIONS	$\frac{3}{8}" = 1'$
AE α -20#	INTERIOR ELEVATIONS	$\frac{3}{8}" = 1'$
AE α -501	WALL MOUNTED WIRING DETAILS	$\frac{3}{4}" = 1'$
AE α -50#	CABLE TRAY MOUNTED RECEPTACLES DETAILS	
AE α -50#	ELECTRICAL DETAILS	
AE α -50#	ELECTRICAL DETAILS	
AE α -601	POWER RISER DIAGRAMS	
AE α -60#	UPS / BPS ONE-LINE DIAGRAM	
AE α -60#	PANEL SCHEDULES AND ELECTRICAL LOAD SUMMARY	
AE α -60#	PANEL SCHEDULES AND ELECTRICAL LOAD SUMMARY	
AE α -701	SCADA SYSTEM BLOCK DIAGRAM NOTES	
AE α -702	SCADA SYSTEM BLOCK DIAGRAMS	

302.5 Non-Accessible Gantry Plans

A separate sub-component plan set must be prepared for each unique gantry toll site. See [Exhibit 302.5-1](#) for details regarding the sheet number protocol.

- (1) One sub-component plan set must be provided for each non-accessible gantry.
- (2) The gantry structure number must be included above the title block.
- (3) The structural and electrical plans and elevations must also identify the mile post and stationing of each toll site gantry.

302.5.1 Non-Accessible Gantry Structural Plans

The following items must be included on the non-accessible gantry structural plans:

- (1) Structural Notes: Identify the toll equipment loads used during design.
- (2) Gantry plan for all interim and ultimate roadway configurations for all TECs.
 - (a) Roadway elements.
 - (b) Structural framing.
 - (c) Location of chord splices.
 - (d) Gantry framing plans showing W-section member layout.
 - (e) Toll equipment layout showing the j-arm positions.
- (3) Gantry elevations showing the roadway cross section at the gantry showing the roadway cross slope and critical roadway elevation reference line for equipment.
 - (a) Centerline of gantry elevation.
 - (b) Pavement elevations at each breakpoint along the roadway cross slope for all interim and ultimate roadway configurations.
 - (c) The APE as identified in **GTR 250.2.2**.
 - (d) Elevations must be recorded in feet to three decimal places.
- (4) Typical cross section of the gantry and truss.
- (5) Truss, upright, and foundation details.
- (6) Gantry upright details.
- (7) J-arm and attachment hardware details.
- (8) Details for mounting the E6 readers (where applicable).

302.5.2 Non-Accessible Gantry Electrical Plans


The following items must be included on the non-accessible gantry electrical plans:

- (1) Electrical gantry plans, sections, and elevations that support the worst-case TEC equipment configuration also accounting for all interim and ultimate roadway configurations, utilizing the appropriate structural gantry plan for the background.
- (2) Details including the following:
 - (a) Gantry section showing longitudinal cable tray in section and equipment cable tray limits also include section of the equipment cable tray with associated supports.
 - (b) Gantry strut channel mounting details.
 - (c) Upright raceway mounting details with wire trough detail.
 - (d) Details for E6 readers & CCTV mounting.
- (3) Lightning protection at the upright base.

302.5.3 Index of Non-Accessible Gantry Plans (each gantry)

The sheet numbering for the toll facility non-accessible gantry plans must be as follows:

Exhibit 302.5-1 Non-Accessible Gantry Sheet Numbering Convention



Assemble the non-accessible gantry plans in the following order and format:

NON-ACCESSIBLE GANTRY STRUCTURAL PLANS

Sheet No.	Sheet Description	Scale
GG#-001	KEY SHEET AND INDEX OF SHEETS	
GS#-001	GENERAL NOTES, SYMBOLS, LEGEND AND ABBREVIATIONS	
GS#-101	GANTRY PLAN NB (OR EB) INTERIM (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN NB (OR EB) INTERIM (TEC 2)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) INTERIM (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) INTERIM (TEC 2)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN NB (OR EB) ULTIMATE (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN NB (OR EB) ULTIMATE (TEC 2)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) ULTIMATE (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) ULTIMATE (TEC 2)	$\frac{1}{8}" = 1'$
GS#-201	GANTRY ELEVATION NB (OR EB) INTERIM	$\frac{1}{8}" = 1'$
GS#-20#	GANTRY ELEVATION SB (OR WB) INTERIM	$\frac{1}{8}" = 1'$
GS#-20#	GANTRY ELEVATION NB (OR EB) ULTIMATE	$\frac{1}{8}" = 1'$
GS#-20#	GANTRY ELEVATION SB (OR WB) ULTIMATE	$\frac{1}{8}" = 1'$
GS#-301	FOUNDATION LAYOUT PLAN	
GS#-30#	FOUNDATION NOTES AND DETAILS	
GS#-30#	REPORT OF CORE BORINGS	
GS#-401	TYPICAL SECTION	$\frac{1}{2}" = 1'$
GS#-40#	ENLARGED TYPICAL SECTION	$1" = 1'$
GS#-40#	TABLE OF VARIABLES	
GS#-501	RACEWAY MOUNTING PLANS	$\frac{1}{8}" = 1'$
GS#-50#	VERTICAL RACEWAY SUPPORT DETAILS	
GS#-50#	MISCELLANEOUS DETAIL(S)	
GS#-801	EQUIPMENT SUPPORT ARM NOTES	
GS#-80#	EQUIPMENT SUPPORT ARM DETAIL(S)	

NON-ACCESSIBLE GANTRY ELECTRICAL PLANS

Sheet No.	Sheet Description	Scale
GE#-001	ELECTRICAL SYMBOLS, LEGEND, AND ABBREVIATIONS	
GE#-002	ELECTRICAL GENERAL NOTES	
GE#-101	GANTRY ELECTRICAL PLAN(S)	$\frac{1}{8}" = 1'$
GE#-501	GANTRY RACEWAY MOUNTING DETAIL(S)	$\frac{1}{2}" = 1'$
GE#-50#	UPRIGHT RACEWAY DETAIL(S)	$\frac{1}{4}" = 1'$
GE#-50#	UPRIGHT STRUT CHANNEL MOUNTING DETAIL(S)	$\frac{1}{4}" = 1'$
GE#-50#	WIRE TROUGH LAYOUT AND DETAIL(S)	$\frac{3}{4}" = 1'$
GE#-50#	E6 READER MOUNTING DETAIL(S)	$\frac{1}{2}" = 1'$
GE#-50#	MISCELLANEOUS GANTRY ELECTRICAL DETAIL(S)	
GE#-50#	GANTRY LIGHTNING PROTECTION DETAIL(S)	

302.6 Accessible Gantry Plans

A separate sub-component plan set must be prepared for each unique gantry toll site. See [Exhibit 302.6-1](#) for details regarding the sheet number protocol.

- (1) One sub-component plan set must be provided for each accessible gantry.
- (2) The gantry structure number must be included above the title block.
- (3) The structural and electrical plans and elevations must also identify the mile post and stationing of each toll site gantry.

302.6.1 Accessible Gantry Structural Plans

The following items must be included on the accessible gantry structural plans:

- (1) Structural Notes: Identify the toll equipment loads used during design. Add shop drawing requirements for accessible gantries similar to the shop drawing notes in Standard Plans 700-041.
- (2) Gantry plans must be provided for all interim and ultimate roadway configurations, showing roadway elements, truss chord splice connections. Gantry plans must also include all toll equipment layouts and the j-arm positions for all TECs. for each interim and the ultimate roadway configurations.
- (3) Truss framing plans, and elevations.
- (4) Grating plans for upper and lower grating.
- (5) Post layout plans.
- (6) Truss cross section.
- (7) Chord splice connection.
- (8) Truss, upright, and foundation details.
- (9) Gantry upright details.
- (10) J-arm and attachment hardware details.
- (11) Equipment retraction assembly inclusive of gate posts, gear box layouts, toll equipment maintenance and operational clearances, etc.
- (12) Details for the gantry columns and uprights, foundations, gear boxes, J-arm support arms, latches, grating, stairs, screening, and fall restraints.
- (13) Details for mounting the E6 readers.

- (14) Gantry Elevations showing the roadway cross section at the gantry, the roadway cross slope and critical roadway elevation reference line for equipment.
 - (a) Centerline of gantry elevation.
 - (b) Pavement elevations at each breakpoint along the roadway cross slope for all interim and ultimate roadway configurations.
 - (c) The APE as identified in **GTR 250.2.2**.
 - (d) Elevations must be recorded in feet to three decimal places.
- (15) Typical cross section of the gantry and truss.

302.6.2 Accessible Gantry Electrical Plans


The following items must be included on the accessible gantry electrical plans:

- (1) Electrical gantry plans and sections that support the TEC equipment configurations for the worst-case condition for all interim and ultimate roadway configurations, utilizing the appropriate structural gantry plan for the background.
- (2) E6 enclosure elevation and section.
- (3) Wireway to cable tray transitions and shrouds.
- (4) Details for longitudinal cable tray and transverse cable tray
- (5) Stair and rope lighting details.
- (6) Upright wireway mounting details with wire trough detail.
- (7) Upright strut channel mounting details.
- (8) Lightning protection at the upright base.

302.6.3 Index of Accessible Gantry Plans (each gantry)

The sheet numbering for the toll facility accessible gantry plans must be as follows:

Exhibit 302.6-1 Accessible Gantry Sheet Numbering Convention



Assemble the accessible gantry plans in the following order and format:

ACCESSIBLE GANTRY STRUCTURAL PLANS

Sheet No.	Sheet Description	Scale
GG#-001	KEY SHEET AND INDEX OF SHEETS	
GS#-001	GENERAL NOTES, SYMBOLS, LEGEND AND ABBREVIATIONS (1 of #)	
GS#-00#	GENERAL NOTES, SYMBOLS, LEGEND AND ABBREVIATIONS (2 of #)	
GS#-101	GANTRY PLAN NB (OR EB) INTERIM (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN NB (OR EB) INTERIM (TEC 2)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) INTERIM (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) ULTIMATE (TEC 2)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN NB (OR EB) ULTIMATE (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN NB (OR EB) ULTIMATE (TEC 2)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) ULTIMATE (TEC 1)	$\frac{1}{8}" = 1'$
GS#-10#	GANTRY PLAN SB (OR WB) ULTIMATE (TEC 2)	$\frac{1}{8}" = 1'$
GS#-201	GANTRY ELEVATION NB (or EB) INTERIM	$\frac{1}{8}" = 1'$
GS#-20#	GANTRY ELEVATION SB (OR WB) INTERIM	$\frac{1}{8}" = 1'$
GS#-20#	GANTRY ELEVATION NB (OR EB) ULTIMATE	$\frac{1}{8}" = 1'$
GS#-20#	GANTRY ELEVATION SB (OR WB) ULTIMATE	$\frac{1}{8}" = 1'$
GS#-301	FOUNDATION LAYOUT PLAN(S)	
GS#-30#	FOUNDATION NOTES AND DETAILS	
GS#-30#	REPORT OF CORE BORINGS	
GS#-311	COLUMN A, B, AND C BASE CONNECTION DETAILS	
GS#-31#	COLUMN D BASE CONNECTION DETAILS	
GS#-31#	PEDESTAL DETAILS	$\frac{3}{8}" = 1'$

ACCESSIBLE GANTRY STRUCTURAL PLANS (continued)

Sheet No.	Sheet Description	Scale
GS#-401	COLUMN ELEVATIONS	
GS#-40#	COLUMN A AND C LOWER CHORD CONNECTION	
GS#-40#	COLUMN A AND C UPPER CHORD CONNECTION	
GS#-40#	COLUMN B LOWER CHORD CONNECTION	
GS#-40#	COLUMN B UPPER CHORD CONNECTION	
GS#-40#	PLATFORM DETAILS (1 of 4)	
GS#-40#	PLATFORM DETAILS (2 of 4)	
GS#-40#	PLATFORM DETAILS (3 of 4)	
GS#-40#	PLATFORM DETAILS (4 of 4)	
GS#-410	TRUSS FRAMING (1 OF 2)	
GS#-41#	TRUSS FRAMING (2 OF 2)	
GS#-41#	TRUSS CONNECTION DETAILS (1 of 2)	
GS#-41#	TRUSS CONNECTION DETAILS (2 of 2)	
GS#-41#	TYPICAL SECTION	
GS#-41#	CAMBER AND SPLICE DETAILS	
GS#-501	UPPER GRATING PLAN(S) (MAIN SPAN)	$\frac{1}{8}" = 1'$
GS#-50#	LOWER GRATING PLAN(S) (MAIN SPAN)	$\frac{1}{8}" = 1'$
GS#-50#	UPPER GRATING DETAILS	
GS#-50#	LOWER GRATING DETAILS (1 OF 2)	
GS#-50#	LOWER GRATING DETAILS (2 OF 2)	
GS#-51#	UPPER PLATFORM MAIN POST LAYOUT(S) – INTERIM(S)	$\frac{1}{8}" = 1'$
GS#-51#	UPPER PLATFORM MAIN POST LAYOUT(S) - ULTIMATE	$\frac{1}{8}" = 1'$

ACCESSIBLE GANTRY STRUCTURAL PLANS (continued)

Sheet No.	Sheet Description	Scale
GS#-531	SCREEN PANEL DETAILS (1 of 5)	
GS#-53#	SCREEN PANEL DETAILS (2 of 5)	
GS#-53#	SCREEN PANEL DETAILS (3 of 5)	
GS#-53#	SCREEN PANEL DETAILS (4 of 5)	
GS#-53#	SCREEN PANEL DETAILS (5 of 5)	
GS#-53#	UPPER PLATFORM END FENCING DETAILS (1 of 2)	
GS#-53#	UPPER PLATFORM END FENCING DETAILS (2 of 2)	
GS#-53#	FALL RESTRAINT DETAILS	
GS#-801	J-ARM AND GEAR BOX GENERAL NOTES	
GS#-80#	GEAR BOX DETAILS	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (1 of 18)	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (2 of 18)	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (3 of 18)	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (4 of 18)	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (5 of 18)	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (6 of 18) (TEC 1)	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (6 of 18) (TEC 2)	
GS#-80#	EQUIPMENT SUPPORT ARM DETAILS (7 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (8 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (9 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (10 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (11 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (12 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (13 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (14 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (15 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (16 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (17 of 18)	
GS#-8##	EQUIPMENT SUPPORT ARM DETAILS (18 of 18)	

ACCESSIBLE GANTRY ELECTRICAL PLANS

Sheet No.	Sheet Description	Scale
GE#-001	ELECTRICAL SYMBOL LEGEND AND ABBREVIATIONS	
GE#-002	ELECTRICAL GENERAL NOTES	
GE#-101	GANTRY ELECTRICAL PLAN(S)	$\frac{1}{8}" = 1'$
GE#-10#	ENLARGED GANTRY ELECTRICAL PLAN(S)	$\frac{1}{2}" = 1'$
GE#-501	E6 READER MOUNTING DETAIL(S)	
GE#-50#	CABLE TRAY INSTALLATION DETAIL(S)	
GE#-50#	WIREWAY INSTALLATION DETAIL(S)	
GE#-50#	STAIR AND ROPE LIGHT DETAIL(S)	
GE#-50#	GANTRY UPRIGHT WIREWAY SUPPORT	$\frac{1}{4}" = 1'$
GE#-50#	GANTRY UPRIGHT WIREWAY	$\frac{1}{4}" = 1'$
GE#-50#	WIRE TROUGH LAYOUT AND DETAIL(S)	
GE#-50#	GANTRY LIGHTNING PROTECTION DETAIL(S)	

303 Phase Submittals for Conventional Projects

303.1 General

The development of the toll facilities plans must be organized into phase submittals that is consistent with **FDM** and as described below. The toll facilities plans are composed of several sub-component sets that define the scope of work and are the permit plan sets submitted to the State Fire Marshal's office and building inspector. Each toll facilities sub-component set as defined in **GTR 302** must be submitted, in their entirety, (to the appropriate level of completion), for review at each phase submittal. [Exhibit 303.1-1](#) summarizes the plan's sheet status for each submittal. Phases are not complete until all review comments have been resolved and documented.

FTE has final authority over all design document reviews related to the toll site infrastructure.

Exhibit 303.1-1 Summary of Phase Submittals for Conventional Projects

Provide the listed sub-component sets as applicable:

ITEM	PHASE I	PHASE II	PHASE III	PHASE IV
Toll facility plans				
Master key sheet and sub-component key sheets	P	P	C	F
Demolition / Renovation		P	C	F
Site civil	P	P	C	F
Site electrical	P	P	C	F
Architectural (building)	P	P	C	F
Structural (building)		P	C	F
Mechanical / plumbing (building)		P	C	F
Electrical (building)		P	C	F
Structural (non-accessible / accessible gantry)	P	P	C	F
Electrical (non-accessible / accessible gantry)		P	C	F
Engineer's Estimate		P	C	F
Design analysis reports (mechanical and electrical)		P	C	F
KMZ/KML files- civil, electrical, utility / communications. (site plans)		P	C	F
Technical Special Provision sections		P	C	F
Modified Special Provision(s)		P	C	F
Toll Siting Technical Memorandum	See GTR 300.1			

Status Key:

P – Preliminary

C – Complete but subject to change

F – Final

303.2 Phase I Submittal

The following elements are required for a Phase I (30%) plans submittal.

MASTER KEY SHEET

- Key sheet and index of sheets
- Signature sheet(s)

DEMOLITION PLANS (BUILDING)

- Key sheet and index of sheets
- General notes
- Site demolition plan(s)

SITE CIVIL PLANS

- Key sheet and index of sheets
- General notes
- Overall civil site plan
- Enlarged site plan(s)

SITE ELECTRICAL PLANS

- Symbol legend and abbreviations
- General notes
- Overall electrical site plan

ARCHITECTURAL PLANS (BUILDING)

- Key sheet and index of sheets
- Symbol legend and abbreviations
- General notes and building code data
- Floor Plan(s)

NON-ACCESSIBLE GANTRY STRUCTURAL PLANS

- Key sheet and index of sheets
- General notes
- Plan(s)
- Foundation layout plan

ACCESSIBLE GANTRY STRUCTURAL PLANS

- Key sheet and index of sheets
- General notes
- Plan(s)
- Foundation layout plan

303.3 Phase II Submittal

The following elements in addition to the Phase I (30%) plans submittal are required for a Phase II (60%) plans submittal.

TOLL SITE MASTER KEY SHEET

- Key sheet and index of sheets

DEMOLITION PLANS (BUILDING)

- Floor demolition plan(s)
- Island / Lane demolition plan(s)
- Canopy / building demolition elevations (all sides)
- Structural demolition plan(s)
- Electrical site(s) demolition plan(s)
- Electrical demolition plan(s)
- Tunnel demolition plan(s) (includes electrical / mechanical / systems)
- Power riser diagram(s)
- Electrical panel schedules

SITE CIVIL PLANS

- Pay items
- Typical site details

SITE ELECTRICAL PLANS

- Enlarged Electrical site plan(s)
- Lightning protection plan(s)
- Conduit and pull box details
- Miscellaneous site electrical details

ARCHITECTURAL PLANS (BUILDING)

- Reflected ceiling plan(s)
- Roof plan(s)
- Exterior building elevations (all four walls) and color schedule
- Wall section(s) and details
- Door details
- Door, hardware, and finish schedules

STRUCTURAL PLANS (BUILDING)

- General notes
- Foundation plan and sections
- Roof plan and section(s)
- Exterior elevations (all four walls)
- Section(s) and detail(s)

MECHANICAL / PLUMBING PLANS (BUILDING)

- AC floor plan(s)
- AC equipment details and schedules
- Generator plan, elevations, details, and notes

ELECTRICAL PLANS (BUILDING)

- Symbol legend, abbreviations, and fixture schedule
- Power distribution system plan(s)
- Lighting and systems plans
- Lightning protection plan and details
- Security / Access control system plans, details, and riser diagrams
- CCTV system plan(s), details, and riser diagrams
- Interior elevations - all wall mounted equipment and conduit (all four walls)
- Tolling equipment raceway plan and details
- Miscellaneous electrical detail(s)
- Power riser diagram(s)
- Panelboard schedules and load summary
- SCADA system plan, notes, block diagrams and details

NON-ACCESSIBLE GANTRY STRUCTURAL PLANS

- Elevation(s)
- Foundation notes and details
- Pile data table (if pile foundations are used)
- Report of core borings
- Table of variables
- Toll equipment layout plans
- Wireway mounting plans and details
- Truss section and details
- Toll equipment mounting details

NON-ACCESSIBLE GANTRY ELECTRICAL PLANS

- Electrical symbol legend and abbreviations
- General notes
- Toll equipment and wireway plans
- Power conductor routing details
- Toll equipment cable routing & miscellaneous detail(s)

ACCESSIBLE GANTRY STRUCTURAL PLANS

- Elevation(s)
- Foundation notes and details
- Report of core borings
- Columns to base connections
- Median concrete barrier (if required)
- Pedestal details
- Column elevations
- Column connection – Lower Chord
- Column connection – Upper Chord
- Access platform / stair details
- Truss framing – upper and lower chord plans, and elevations
- Truss connection details
- Typical section
- Camber and splice details
- Upper and lower grating plan(s)
- Upper and lower grating details
- Upper platform main post layout(s) – interim and ultimate
- Wireway mounting details
- Aluminum shroud details
- Screen panel details
- Upper platform end fencing details
- Fall restraint details
- Toll equipment layout plan(s) – interim and ultimate (both TECs)
- J-arm and gear box general notes
- Gear box details
- Equipment support arm details

ACCESSIBLE GANTRY ELECTRICAL PLANS

- Electrical symbol legend and abbreviations
- Electrical general notes
- Overall gantry electrical plan
- Enlarged electrical plan(s)
- Raceway layout plan – (accommodates ultimate)
- Electrical details
- E6 wireway installation details
- Column wireway support details
- Access platform / stair lighting plan and details
- Lightning protection plan

TECHNICAL SPECIAL PROVISION AND MODIFIED SPECIAL PROVISION

- TSP Table of Contents
- List of MSP sections

ENGINEER'S ESTIMATE

- Engineer's estimate for each toll site using the FTE template

GTR DEVIATIONS

- All approved and rejected GTR Deviations identified during design development must be included with the Final TSTM. All deviation forms must be complete and include the appropriate FTE staff's signatures.

303.4 Phase III Submittal

The following elements in addition to the Phase II (60%) plans submittal are required for a Phase III (90%) plans submittal.

SITE CIVIL PLANS

- Grading plan(s)
- Rigid concrete pavement joint layout within the toll loop pavement area

SITE ELECTRICAL PLANS

- Loop conduit stub-up in lanes for rigid concrete pavement
- Loop conduit stub-up locations along the concrete barrier for flexible pavement

TECHNICAL SPECIAL PROVISION AND MODIFIED SPECIAL PROVISION

- TSP sections
- Track changes version of TSP Sections in MS word (See **GTR 307**)
- MSP sections

303.5 Phase IV Submittal

Unless otherwise directed by FTE, all elements required to provide a complete design must be included in the Phase IV (100%) plans submittal. Phase IV submission represents a 100% complete design.

- New service connection commitments from the electrical service provider as per **GTR 232.2**

303.6 Permit Plans

Permit plans submission must be in accordance with the requirements stated in **GTR 270** and the **TSP Section for Permits**.

304 Phase Submittals for Non-Conventional Projects

304.1 General

Modification for non-conventional projects:

Delete **GTR 303** and follow **GTR 304**.

The development of the toll facility plans must be organized into phase submittals as described below. The toll facility plans are composed of several sub-component plan sets that define the scope of work and are the permit plans sets submitted to the State Fire Marshal's Office and building inspector. Each toll site sub-component set as defined in **GTR 302** must be submitted in their entirety for review at each phase submittal. All sub-component sets must be submitted in their entirety. Piecemeal submittals are not acceptable for submittal or review.

[Exhibit 304.1-1](#) summarizes the plans sheet status required for each submittal. Phases are not complete until all review comments have been resolved and documented. FTE has final authority over all design document reviews related to the toll point infrastructure.

Exhibit 304.1-1 Summary of Phase Submittals for Non-Conventional Projects

Provide the listed sub-component sets as applicable:

ITEM	TECHNICAL PROPOSAL	90% PLANS	FINAL PLANS
Toll facility plans			
Master key sheet and sub-component key sheets	P	C	F
Demolition		P	F
Site civil	P	C	F
Site electrical	P	C	F
Architectural (building plans)	P	C	F
Structural (building plans)		C	F
Mechanical / plumbing (building plans)		C	F
Electrical (building plans)		C	F
Structural (non-accessible / accessible gantry)	P	C	F
Electrical (non-accessible / accessible gantry)		C	F
Schedule of Values		C	F
Design analysis reports (mechanical and electrical)		C	F
KMZ/KML files - civil, electrical, utility / communication (site plans)	P	C	F
Technical Special Provision sections	P	C	F
Modified Special Provision(s)		C	F

Status Key:

P – Preliminary

C – Complete but subject to change

F – Final

304.2 Technical Proposal Submittal

The following plans are required at a minimum for the technical proposal submittal.

MASTER KEY SHEET

- (1) **GTR** criteria version used for design
- (2) Toll facilities master key sheet
- (3) Toll facilities signature sheet(s)
- (4) Toll facility sub-component plans (a separate key sheet for each*)

*Each key sheet shall be a copy of the master key sheet except for the following changes:

- Identify the toll facilities engineer(s) and/or architect of record.
- Uniquely identify the sub-component set within the project.
- Identify the index of plans for that sub-component set.

SITE CIVIL PLANS

- Key sheet and index of sheets
- General notes
- Overall civil site plan
- Site plan(s)

SITE ELECTRICAL PLANS

- Symbol legend and abbreviations
- General notes
- Overall electrical site plan(s)
- Electrical site plan(s)

ARCHITECTURAL PLANS (BUILDING)

- Key sheet and index of sheets
- Symbol legend and abbreviations
- General notes and building code data
- Floor plan(s)

NON-ACCESSIBLE GANTRY STRUCTURAL PLANS

- Key sheet and index of sheets
- General notes
- Plan(s)
- Elevation(s)
- Foundation layout plan(s)

ACCESSIBLE GANTRY STRUCTURAL PLANS

- Key sheet and index of sheets
- General notes
- Plan(s)
- Elevation(s)
- Foundation layout plan(s)

TECHNICAL SPECIAL PROVISION AND MODIFIED SPECIAL PROVISION

- TSP sections
- Track changes version of TSP Sections in MS word (See **GTR 307**)
- MSP sections

TSTM and GTR Deviations

- Approved and rejected deviations are included with the TSTM provided in the RFP. The TSTM is specific to the toll site location(s) and may only be changed through the ATC process. All criteria must be re-evaluated per **GTR Part 2**. Any associated deviations must be submitted for review and approval prior to developing the 90% plans submittal.
- FTE approved GTR Deviations associated with the revised TSTM.

304.3 90% Plans Submittal

The following elements in addition to the technical proposal submittal are required for a 90% plans submittal.

DEMOLITION PLANS

- Key sheet and index of sheets
- General notes
- Site demolition plan(s)
- Floor demolition plan(s)
- Island / lane demolition plan(s)
- Canopy / building demolition elevations (all sides)
- Structural demolition plan(s)
- Electrical site(s) demolition plan(s)
- Electrical demolition plan(s)
- Tunnel demolition plan(s) (includes electrical / mechanical / systems)
- Power riser diagram(s)
- Electrical panel schedules

SITE CIVIL PLANS

- Typical site details
- Grading plan(s)
- Rigid concrete pavement joint layout within the toll loop pavement area (when applicable)

SITE ELECTRICAL PLANS

- Loop conduit stub-up in lanes (for rigid concrete pavement)
- Loop conduit stub-up locations along the concrete barrier for flexible pavement
- Lightning protection plan(s)
- Conduit and pull box details
- Miscellaneous site electrical details

ARCHITECTURAL PLANS (BUILDING)

- Reflected ceiling plan(s)
- Roof plan(s)
- Exterior building elevations (all four walls) and color schedule
- Wall section(s) and details
- Door details
- Door, hardware, and finish schedules

STRUCTURAL PLANS (BUILDING)

- General Notes
- Foundation plans and details
- Roof plan and section(s)
- Exterior elevations (all four walls)
- Section(s) and detail(s)

MECHANICAL / PLUMBING PLANS (BUILDING)

- AC floor plan(s)
- AC equipment detail(s) and schedule(s)
- Generator plan, elevation(s), detail(s), and notes

ELECTRICAL PLANS (BUILDING)

- Symbol legend, abbreviations, and fixture schedule
- Power distribution system plan(s)
- Lighting and systems plans
- Lightning protection plan and details
- Security / Access control system plans, details, and riser diagrams
- CCTV system plan(s), details, and riser diagram(s)
- Interior elevations - all wall mounted equipment and conduit (all four walls)
- Tolling equipment raceway plan and detail(s)
- Miscellaneous electrical detail(s)
- Power riser diagram(s)

ELECTRICAL PLANS (BUILDING) (Continued)

- Panelboard schedules and load summary
- SCADA system plan, notes, block diagram and details

NON-ACCESSIBLE GANTRY STRUCTURAL PLANS

- General Notes
- Gantry plans(s)
- Gantry elevation(s)
- Foundation notes and detail(s)
- Pile data table (if pile foundations are used)
- Table of variables
- Toll equipment layout plan(s)
- Wireway mounting plan(s) and detail(s)
- Truss section and detail(s)

NON-ACCESSIBLE GANTRY ELECTRICAL PLANS

- Electrical symbols, legend, and abbreviations
- General notes
- Toll equipment and wireway plans
- Power conductor routing details
- Toll equipment cable routing details
- Miscellaneous detail(s)

ACCESSIBLE GANTRY STRUCTURAL PLANS

- Connection detail(s)
- Column elevation(s)
- Column connection – lower chord
- Column connection – upper chord
- Platform / stair column detail(s)
- Main truss – upper and lower chord plans and elevation(s)
- Truss connection detail(s)

ACCESSIBLE GANTRY STRUCTURAL PLANS (Continued)

- Typical section(s)
- Truss chord camber and splice detail(s)
- Upper and grating plan(s)
- Grating detail(s)
- Upper platform main post layout(s)
- Screen panel detail(s)
- Upper platform end fencing detail(s)
- Fall restraint detail(s)
- Column and wireway mounting detail(s)
- Toll equipment layout plan(s)
- Tolling equipment general notes
- Equipment support arm detail(s)

ACCESSIBLE GANTRY ELECTRICAL PLANS

- Electrical symbol legend and abbreviations
- Electrical general notes
- Overall gantry electrical plan
- Enlarged electrical plan(s)
- Raceway layout plan – (accommodates ultimate)
- Electrical details
- E6 wireway installation details
- Column wireway support details
- Access platform / stair lighting plan and details
- Lightning protection plan

TECHNICAL SPECIAL PROVISION AND MODIFIED SPECIAL PROVISION

- Complete TSP sections
- Complete MSP sections

304.4 Final Plans Submittal

All elements required to provide a complete design must be included in the final submittal.

304.5 Permit Plans

Permit plans submission must be in accordance with the requirements stated in **GTR 270** and the **TSP Section for Permits**.

305 Design Analysis Reports

305.1 General

The toll site construction plans must be accompanied by a design analysis report for the mechanical systems, electrical systems, TEB foundation, TEB, and gantry structures. Structural and geotechnical calculations must be in accordance with the FDOT

305.2 Mechanical Design

The design of all toll site mechanical systems must comply with Florida Administrative Code (FAC) 61G15-34, Responsibility Rules of Professional Engineers Concerning the Design of Mechanical Systems, along with all applicable building codes. This applies to new projects and any major modifications or renovations.

- (1) Building load analysis and equipment selection:
 - (a) An itemized AC computation design values summary sheet must be provided separate from what is provided in the load calculations. This summary sheet must include building “U” values, design conditions per American Society of Heating and Air-conditioning Engineers (ASHAE), internal building heat loads, and proposed equipment cut sheets including accessories. A standalone itemized list must of these project design values per equipment / heat source must be provided as part of the AC calculations submittal package.
 - (b) Itemized heat gain calculations must be provided to determine required cooling load and air movement requirements to effectively control the temperature and humidity in the TEB. Site-specific heat gain calculations must be provided to justify the cooling capacities of equipment selected. These calculations must be submitted to FTE for review and approval prior to final design.
 - (c) Preliminary calculations must account for heat generated by tolling equipment and tolling communications located in their respective cabinets heat output rate provided in **GTR 245.2**.
- (2) Fuel oil piping
 - (a) The EOR must ensure the head loss within the fuel piping to and from the generator and fuel tank does not exceed the capacity of the generator fuel pump. The calculation must include consideration for changes in elevation and all fittings including but not limited to strainers, anti-siphon devices and valves.

- (b) For existing installations, new calculations are required if the generator pump is modified or changes in location or elevation occur as required by the project scope.

305.3 Electrical Design

The power design analysis report must be provided and must comply with the following requirements:

- (1) Coordinate with the power service providers (PSP) during the design of the site. Each provider contact's name and telephone number must be placed in the electrical design analysis report and on the released for construction electrical plans.
- (2) The design of electrical power distribution and lighting systems must comply with Florida Administrative Code (FAC) 61G15-33, Responsibility Rules of Professional Engineers Concerning the Design of Electrical Systems. This applies to new projects, modifications, or renovations. Design drawings and design analysis reports must be prepared, reviewed, and signed and sealed by a professional engineer licensed in the State of Florida. The professional engineer must be competent in electrical engineering through training and experience.
- (3) The plans and reports must be submitted to FTE for review and approval with the Phase III (90%) submittal. The design of the associated plans beyond Phase III (90%) must not proceed until all review comments have been resolved and FTE has approved the design analysis reports. The reports must include all formulas, calculations, variables, mathematical substitutions, and data used to obtain the results. Reports must include, at a minimum, the calculations listed below:
 - (a) Voltage drop calculations must be submitted for all branch circuits, feeders, and service entrance conductors beginning at the utility transformer secondary terminals. The voltage drop must be limited to the percentages outlined in the FBC.
 - (b) Calculations to determine the load, in volt-amps and amps, using the design loads for each feeder, branch circuit, panelboard, and at the service entrance point must be submitted. Demand factors must be applied in accordance with **Article 220** of the **NEC**. The results are used to size conductors, circuit breakers, and in voltage drop calculations.
 - The calculated load at the service entrance point must be shown on the power distribution system riser diagram in the electrical plans. Load calculations for power distribution system modifications or renovations must consist of the highest existing measured load (prior to modification), the load being removed, the load being added, and the new total calculated load.

- Existing loads must be field verified by metering or utility information as outlined in **Article 220.87** of the **NEC**. New service points and distribution equipment must be designed with at least 20% spare capacity in amperes.
- (c) Short circuit calculations must be submitted that show the available RMS fault currents, line to line, and line to ground at ½ cycle after the fault occurs. These calculations must be performed in accordance with the recommendations in the most recent edition of **IEEE Standard 141, Electrical Power Distribution Systems for Industrial Plants**.
- The calculations for faults must be performed at each panelboard, automatic transfer switch, and protective device including UPS and UPS maintenance bypass.
 - These calculated values must be shown on the power distribution system riser diagram in the electrical plans and used to select the interrupting capacity of each protective device, panelboard(s), and ATS to withstand ratings.
 - Documentation received from the utility provider must be provided showing the maximum available fault current at the utility transformer secondary terminals. This value must be used in the short circuit analysis. The short circuit analysis must be updated if a major modification or renovation takes place.
- (4) Electrical distribution equipment must be designed as fully rated, sufficiently, and selectively coordinated systems.
- (a) Time / current curves must be submitted showing selective coordination of the overcurrent devices.
- (b) A preliminary coordination study must be performed using a recognized software program to confirm that the specified protective devices safely interrupt electrical faults and overloads and isolate them from the smallest portion of the electrical system to minimize outages. Only the closest protective device to the fault must operate to isolate the fault without affecting other parts of the system.
- (c) A fault current and coordination study must be prepared for any project that proposes a new or replacement panelboard.
- (5) Generator sizing calculations and computer simulation printouts must be submitted that show the selected engine generator at each site meets the environmental and electrical requirements described in **GTR Part 2, Appendix 1, TSP Section for Engine Generators**. Catalog cut sheets or specification sheets must be included that show the selected engine generator's following information:
- (a) Complete model number
 - (b) Accessories

- (c) EPA exhaust tier level
 - (d) Noise data at 7 meters
 - (e) Weather protective enclosure information
 - (f) Dimensional data
 - (g) Fuel consumption rates
- (6) Generator size and adequacy must be recalculated and confirmed if any alterations are made to existing emergency power systems.
- (7) Photometric calculations for interior lighting must be provided to meet the requirements of **GTR 242.2**.

306 Pay Items

306.1 General

- (1) Lump sum pay items for work at each toll site are identified in the Basis of Estimates (BOE). Common toll pay items are as follows:
 - (a) New Construction – Toll Plaza
 - (b) Modifying Existing or Phased Demolition – Toll Plaza (Modify Existing)
 - (c) Toll Plaza Island / Lane Work – Toll Plaza Island
 - (d) Total Site Demolition – Clearing and Grubbing
- (2) The lump sum pay item for new construction includes, but is not limited to the following:
 - (a) TEB, and all architectural, structural, mechanical, and electrical components shown in the contract documents
 - (b) Toll equipment gantry and all structural mechanical, and electrical components shown in the contract documents
 - (c) Communications cabinet, conduit, pull boxes, wireways, wire troughs required for tolling as shown in the contract documents
 - (d) Emergency generator and fuel tank as shown in the contract documents
 - (e) Transformer, generator, fuel tank, ground-mounted E6 enclosure pads as shown in the contract documents
 - (f) Concrete sidewalk within the toll site envelope
 - (g) Utility service connections as shown in the contract documents
 - (h) Utility modifications or relocations as shown in the contract documents
 - (i) Dewatering as necessary to facilitate construction
- (3) The lump sum pay items for modifying existing toll sites and for total site demolition must include the following:
 - (a) Detailed notes identifying items that are included in the lump sum
 - (b) Detailed notes identifying items that are paid under roadway pay items in the FDOT BOE

- (4) There are items associated with toll site construction that must be paid under the various roadway pay items in the FDOT BOE. All quantities for these pay items must be coordinated with the roadway EOR including, but not limited to the following:
- (a) Roadway pavement (including the tolling pavement area)
 - (b) Median concrete barrier
 - (c) Shoulder concrete barrier
 - (d) Guardrail
 - (e) Sodding at each toll site
 - (f) Earthwork
 - (g) Fencing
 - (h) Traffic control
 - (i) Retaining walls (any type)
 - (j) CIAC for primary power
 - (k) Removal of concrete pavement, sidewalks, slabs, etc.
 - (l) Delivery of salvageable material
 - (m) Flowable fill

Modification for Non-Conventional Projects:

Delete **GTR 306.1** and replace with the following:

306.1 General

Detailed notes and lists of pay items are not required.

307 Technical Special Provision Sections Updates

307.1 General

- (1) Prepare and submit all TSP Sections in Microsoft Word© format.
- (2) Page numbering of the TSP Sections must be in accordance with the requirements presented in Section 3 of the FDOT [Specifications Handbook](#).
- (3) Track all changes and highlight proposed updates made to the TSP Sections as provided in **GTR Part 2, Appendix 1**.
- (4) Contact manufacturers of all items specified in Level 2 and Level 3 TSP sections to determine the availability of items and model numbers.
- (5) Provide the above at Phase III plan submittal and all subsequent submittals.

Modification for Non-Conventional Projects:

Delete **Item 5** above and replace with the following:

- (5) Provide the above at the 90% Plans submittal and all subsequent submittals.

308 Shop Drawings

308.1 General

- (1) Shop drawings for toll sites must be identified in the individual TSP Sections included in the contract documents.
- (2) See TSP Sections provided in **GTR Part 2, Appendix 1** for shop drawing submittal requirements.
- (3) Turnpike Shop Drawings Procedures must be followed. These procedures are available at:
<http://www.floridasturnpike.com/design/disciplines/shopdrawingprocessinq.html>